



Product Service

Technical Report No. 028-71375881-2
dated 2010-10-22

**Choose certainty.
Add value.**

Client: Jensen Swing Productions Inc.
Wheatlands Rd 9327
Ciraolo, Charvet
US 92071 Santee

Manufacturing location: No information available

Test object: Swing seat S 115

Test specifications: EN 1176-2:2008 paragraph 4.6 impact attenuation of seats

Purpose of examination: Test of the impact attenuation and average surface compression of a swing seat for playground swings

Test result: See chapter 4


This technical report may only be quoted in full. Any use for advertising purposes must be granted in writing. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production.

1 Description of the test subject

1.1 Function

Swing seat for public use

1.2 Technical data

Item	Weght	Picture
Seat S115	1,83 kg	

2 Order

2.1 Date of Purchase Order

29/07/2010

2.2 Date of receipt of test subject / Sampling date

06/09/2010

3 Test procedure

The swing seat was tested according to the requirements of EN 1176-2:2008 sec. 4.6
 The seat S115 was fixed to a distance of 400 mm between the fixation points of the shackles to obtain a practical situation.
 The seat was suspended with 6 mm standard chains length 240 cm

The seat was elevated to a position of 60° angle of the suspending members, and then released freely. The seat hit the test ball horizontally in line with the center of gravity.



Product Service

The test ball was covered with carbon copy paper to receive the dimension of the contact surface between seat and test ball.

3.1 Test equipment

Testball	
Manufacturer:	HE-Datentechnik
Type	HIC@The Beach 011C
Measuring board	
manufacturer	National Instruments
Type	NI DAQ USB 9215A
Tri-axial accelerometer	
manufacturer:	Entran
Type	EGCS3-A-500

4 Results

Seat	Weight	Acceleration (max. 50g)	contact area	ave. compression (max. 90 N/cm ²)
S115	1,83 kg	24,8 g	10,14 cm ²	44 N/cm ²

5 Remarks:

None

6 Summary:

Seat S115 fulfills the requirements for maximum acceleration and average compression

Project Manager

Checked by

Dipl.-Ing. (FH) Franz Danner
MUC TRF 4

Pictures of the test

